1(2) DATA SHEET



Fire Alarm Cabinet

External Door

Part no. 5100861-00A

G017071

System: TERRA FIRE

General Description

The External Door is a fully transparent door with a plexiglass window.

The External Door is intended to be used with either the Fire Alarm Control Panel or the Distributed Cabinet, when they are used as combined Fire brigade / Evacuation - control panel. The External Door replaces then the ordinary door, so that switches, evacuation panel, and other controls are visible through the plexiglass window.

The External Door is supplied with a keylock for Swedish standard key SS3654 to access the interior.

As standard the External Door comes as a right hinged door (opens from the left), however it is possible to change the hinge direction and turn the key lock around to open it from the right.



G017106

Figure 1. Example of a taylormade fire brigade control panel, equipped with the External Door.

Accessories

Swedish standard keys SS3654

Data

Ambient temperature Max 25 °C

Ambient humidity 0 to 95% RH

Material Stainless steel

Polycarbonate (smoked) Plastic door caps

Colour RAL7035 Weight $3 \text{ kg} \pm 5\%$

Dimensions (H \times W \times D) 670 \times 440 \times 40 mm

Ingress protection IP30
Certified according to

09 2531-CPR-232.1686 DOP no. 6301900

The specifications described herein are subject to change without notice.

Data sheet no. 5100861-00A_External Door_I0_EN_2017_A



DATA SHEET 2(2)

Dimensions (mm)




Figure 2. The supporting crossbars (1) can be moved up or down slightly in order to fit the internal equipment.